



- * SINGLE AUTOLOCK AVAILABLE FROM 1990 SEE ALSO
- * DOUBLE AUTOLOCK AVAILABLE FROM 1994
- * MANUAL LOCK AVAILABLE FROM 1984
- * EARLY MANUAL LOCK AVAILABLE FROM 1980

* VERTICAL SHAFT GEAR FIXING FOR SPIRAL BEVEL GEARS - SBG

* GREASE ALL BUSHES & PIVOT PINS & BALL ON ASSEMBLY WITH DUCKHAMS KODOL GREASE

* USE 'INSTANT GASKET' SILICONE JOINTING COMPOUND ON ALL JOINT & SEALING FACES

* DEGREASE WELL & USE LOCTITE BEARING FIT TO RETAIN ALL BEARINGS AND ON ALL NOSE SLIDING INTERNAL SPLINES

* SHIM TO ADJUST INTERNALLY AS MARKED 'S' WITH SHIMS N° 600 & 605 EXTERNALLY USE GASKET MATERIAL

* SILLETTE SONIC LTD © APRIL 1985

SECTION THREE TYPE 2 CAT DRIVE FITTED WITH SINGLE AUTOLOCK.
 OPTION FOR SPIRAL BEVEL GEARS NOTED AS 'SBG' WITH PART N°
 THE ABOVE SPECIFICATION & DETAILS ARE SUBJECT TO ALTERATION OR MODIFICATION
 WITHOUT PRIOR NOTIFICATION - CHECK BEFORE ORDERING - GOVERNMENT WITHOUT SPEERING LINKS